

Film and dispenser sold separately.



A. General-Purpose Masking Tapes

55m, 3" core.

No.	Width	Rolls/Case	Case
UVS 51301	1" (24 mm)	36	
UVS 51302	2" (48 mm)	24	

3M

B. 3M™ Polyethylene-Coated Cloth Duct Tape

For repairing flexible hoses and sealing heat or A/C vents. UL 723 Listed. Rubber adhesive. 32-lb. tensile strength. 10.7 mils thick. Silver. 3" core. 48mm x 54.8m.

MCO 6969-2	Roll
------------	------



C. Kleencut® Stainless Steel Straight Shears

Rust-resistant, precision ground stainless steel blades with a soft, rubberized grip for comfort. Traditional German design. 6" length, 2¾" cut. Black handles. Manufacturer's ten-year warranty.

ACE 19016	Each
-----------	------

D. Kleen Earth® Straight Shears

Stainless steel blades are sonically welded to 70% recycled plastic handles. 30% post-consumer recycled content. 8" length, 3¼" cut. Black handles. Manufacturer's ten-year warranty.

ACE 41418	Each
-----------	------



E. "Handwrap" Stretch Film

- Wrap pallet loads to ensure safe and secure delivery
- Self-adhering—each layer of film bonds to the next for added strength
- Protects shipments from water, dirt and damage caused by excess movement
- 18" wide rolls with 3" core

15-Micron (60-Gauge) Thickness—For Type A loads to 2,000 lbs. Roll length 2,000 ft. 4 rolls per case. Shpg. wt. 34 lbs.

UVS 62018	Case
-----------	------

20-Micron (80-Gauge) Thickness—For heavier Type B and Type C loads up to 2,500 lbs. Roll length 1,500 ft. 4 rolls per case. Shpg. wt. 35 lbs.


UVS 80118	Case
-----------	------

F. Adjustable Hand Dispenser


Use with stretch film rolls 12" to 18" wide. Adjusts for the strongest tension. Shpg. wt. 4 lbs.

UVS 89000	Each
-----------	------


Check pallet types to determine which stretch film to use.



TYPE A
Square, no protruding edges.



TYPE B
Somewhat square with some voids in pallet.



TYPE C
Protruding boxes and voids on pallet.